

**AMENDMENTS TO THE CLAIMS**

Please cancel claims 35-45 as indicated below.

1. (Previously Presented) A method comprising:  
receiving information indicating a need to change an amount of data being  
transmitted through a first media access control (MAC) device to a client  
of the first MAC device, wherein  
the information is received from the client when the client determines that  
the client is receiving data at a rate exceeding a set threshold;  
forming a message including an indication to a second MAC device to change a  
rate at which the second MAC device transmits data to the client, wherein  
said forming the message uses the information indicating the need to  
change the amount of data being transmitted to the client, and  
a total bandwidth allocation of the first MAC device is unaffected by said  
change; and  
transmitting the message to the second MAC device over a network.
2. (Original) The method of claim 1 wherein the network is a metropolitan area  
network (MAN).
3. (Original) The method of claim 1 wherein the network is a resilient packet  
ring (RPR) network.
4. (Original) The method of claim 1 wherein the network includes a first  
datapath for transmitting data from the first MAC device to the second MAC device, and  
wherein the network includes a second datapath for transmitting data from the second  
MAC device to the first MAC device.
5. (Original) The method of claim 1 wherein the message is a resilient packet  
ring (RPR) fairness message.

6. (Original) The method of claim 1 further comprising:  
determining an extent to which a data buffer associated with the client of the first  
MAC device contains data; and  
preparing the information indicating the need to change the amount of data being  
transmitted through the first MAC device to the client of the first MAC  
device based on the extent to which the data buffer associated with the  
client of the first MAC device contains data.
7. (Original) The method of claim 6 further comprising:  
transmitting, to the first MAC device, the information indicating the need to  
change the amount of data being transmitted through the first MAC device  
to the client of the first MAC device.
8. (Original) The method of claim 1 wherein the message further includes a  
MAC device address.
9. (Original) The method of claim 8 wherein the MAC device address  
corresponds to one of the first MAC device, the second MAC device, and another MAC  
device.
10. (Original) The method of claim 1 wherein the indication to the second MAC  
device to change the rate at which the second MAC device transmits data includes at least  
one of: a MAC device address, a data transmission rate, a ramp factor, and a flag.
11. (Original) The method of claim 1 wherein the indication to the second MAC  
device to change the rate at which the second MAC device transmits data includes a data  
transmission rate, the method further comprising:  
determining the data transmission rate.
12. (Original) The method of claim 11 wherein the determining the data  
transmission rate further comprises at least one of:  
calculating the data transmission rate;

selecting a value for the data transmission rate; and  
determining a ramp factor.

13. (Original) The method of claim 1 further comprising:  
transmitting the message from the second MAC device to a third MAC device.

14. (Original) The method of claim 1 wherein the first MAC device is part of a first resilient packet ring (RPR) station and wherein the second MAC device is part of a second RPR station.

15. (Original) The method of claim 1 wherein the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device includes at least one of: a data transmission rate, a counter value, a message indicating that a buffer threshold has been exceeded, and a signal from the client of the first MAC.

16. (Original) The method of claim 1 wherein:  
the information indicating the need to change the amount of data being  
transmitted through the first MAC device to the client of the first MAC  
device further comprises at least one of: information indicating the need to  
reduce the amount of data being transmitted, and information indicating  
the need to increase the amount of data being transmitted; and  
the indication to the second MAC device to change the rate at which the second  
MAC device transmits data further comprises at least one of: an indication  
to the second MAC device to reduce the rate at which the second MAC  
device transmits data, and an indication to the second MAC device to  
increase the rate at which the second MAC device transmits data.

17. (Previously Presented) The method of claim 1 encoded in a computer readable medium as instructions executable on a processor, the computer readable medium being one of an electronic storage medium, a magnetic storage medium, and an optical storage medium.

18. (Previously Presented) An apparatus comprising:

a first media access control (MAC) device operable to be coupled to a network,  
the first MAC device including control logic configured to prepare a  
message for transmission on the network, wherein  
the message includes an indication to change a rate at which another MAC  
device transmits data to a MAC client coupled to the first MAC  
device, and  
a total bandwidth allocation of the first MAC device is unaffected by said  
change; and  
the MAC client coupled to the first MAC device, wherein the MAC client  
comprises  
a buffer for storing data transmitted to the MAC client and  
buffer control circuitry configured to provide information about an amount  
of data stored in the buffer, wherein  
the control logic is responsive to the information about the amount  
of data stored in the buffer to prepare the message.

19. (Original) The apparatus of claim 18 wherein the network is a metropolitan area network (MAN).

20. (Original) The apparatus of claim 18 wherein the network is a resilient packet ring (RPR) network.

21. (Original) The apparatus of claim 18 further comprising:

a second MAC device, wherein the second MAC device is the another MAC  
device;  
a first datapath coupled between the first MAC device and the second MAC  
device, the first datapath for transmitting data from the first MAC device  
to the second MAC device; and  
a second datapath coupled between the first MAC device and the second MAC  
device, the second datapath for transmitting data from the second MAC  
device to the first MAC device.

22. (Original) The apparatus of claim 21 wherein the first MAC device is further operable to transmit the message to the second MAC device.

23. (Original) The apparatus of claim 21 wherein the second MAC device is configured to transmit the message to a third MAC device.

24. (Original) The apparatus of claim 21 wherein the first MAC device is part of a first resilient packet ring (RPR) station and wherein the second MAC device is part of a second RPR station.

25. (Original) The apparatus of claim 18 wherein the message is a resilient packet ring (RPR) fairness message.

26. (Original) The apparatus of claim 18 wherein the buffer control circuitry is coupled to the control logic, and wherein the control logic is further configured to use the information about the amount of data stored in the buffer to determine the indication to change the rate at which another MAC device transmits data.

27. (Original) The apparatus of claim 18 wherein the message further includes a MAC device address.

28. (Original) The apparatus of claim 27 wherein the MAC device address corresponds to one of the first MAC device and the another MAC device.

29. (Original) The apparatus of claim 18 wherein the indication to change the rate at which another MAC device transmits data includes at least one of: a MAC device address, a data transmission rate, a ramp factor, and a flag.

30. (Original) The apparatus of claim 18 wherein the control circuitry is further configured to determine at least one of a data transmission rate and a data transmission rate ramp.

31. (Original) The apparatus of claim 18 wherein the information about an amount of data stored in the buffer includes at least one of: a data transmission rate, a counter value, a message indicating that a buffer threshold has been exceeded, and a signal from the client of the first MAC.

32. (Original) The apparatus of claim 18 wherein MAC client further comprises packet processing circuitry coupled to the buffer.

33. (Original) The apparatus of claim 32 wherein the packet processing circuitry includes the buffer control circuitry.

34. (Original) The apparatus of claim 18 wherein the indication to change the rate at which another MAC device transmits data further comprises at least one of an indication to reduce the rate at which another MAC device transmits data, and an indication to increase the rate at which another MAC device transmits data.

35-45. **(Cancelled)**

46. (Previously Presented) An apparatus comprising:  
 a first media access control (MAC) device coupled to a network;  
 a client of the first MAC device coupled to the first MAC device;  
 a means for receiving information indicating a need to change an amount of data  
     being transmitted through the first media access control (MAC) device to  
     the client of the first MAC device, wherein  
     the information is received from the client when the client determines that  
     the client is receiving data at a rate exceeding a set threshold;  
 a means for forming a message including an indication to a second MAC device  
     to change a rate at which the second MAC device transmits data to the  
     client, wherein  
     said means for forming the message uses the information indicating the  
     need to change the amount of data being transmitted to the client,  
 and

a total bandwidth allocation of the first MAC device is unaffected by said change; and  
a means for transmitting the message to the second MAC device over the network.

47. (Original) The apparatus of claim 46 wherein the network is at least one of a metropolitan area network (MAN) and a resilient packet ring (RPR) network.

48. (Original) The apparatus of claim 46 wherein the message is a resilient packet ring (RPR) fairness message.

49. (Original) The apparatus of claim 46 further comprising:  
a means for determining an extent to which a data buffer associated with the client of the first MAC device contains data; and  
a means for preparing the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device based on the extent to which the data buffer associated with the client of the first MAC device contains data.

50. (Original) The apparatus of claim 46 wherein the message further includes a MAC device address.

51. (Original) The apparatus of claim 46 wherein the indication to the second MAC device to change the rate at which the second MAC device transmits data includes at least one of: a MAC device address, a data transmission rate, a ramp factor, and a flag.

52. (Original) The apparatus of claim 46 wherein the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device includes at least one of: a data transmission rate, a counter value, a message indicating that a buffer threshold has been exceeded, and a signal from the client of the first MAC.

53. (Original) The apparatus of claim 46 wherein:  
the information indicating the need to change the amount of data being  
transmitted through the first MAC device to the client of the first MAC  
device further comprises at least one of: information indicating the need to  
reduce the amount of data being transmitted, and information indicating  
the need to increase the amount of data being transmitted; and  
the indication to the second MAC device to change the rate at which the second  
MAC device transmits data further comprises at least one of: an indication  
to the second MAC device to reduce the rate at which the second MAC  
device transmits data, and an indication to the second MAC device to  
increase the rate at which the second MAC device transmits data.

54. (Previously Presented) A computer readable medium comprising program  
instructions executable on a processor, the computer readable medium being at least one  
of an electronic storage medium, a magnetic storage medium, and an optical storage  
medium, wherein the program instructions are operable to implement each of:  
receiving information indicating a need to change an amount of data being  
transmitted through a first media access control (MAC) device to a client  
of the first MAC device, wherein  
the information is received from the client when the client determines that  
the client is receiving data at a rate exceeding a set threshold;  
forming a message including an indication to a second MAC device to change a  
rate at which the second MAC device transmits data to the client, wherein  
said forming the message uses the information indicating the need to  
change the amount of data being transmitted to the client, and  
a total bandwidth allocation of the first MAC device is unaffected by said  
change; and  
transmitting the message to the second MAC device over a network.



55. (Original) The computer readable medium of claim 54 wherein the network is at least one of a metropolitan area network (MAN) and a resilient packet ring (RPR) network.

56. (Original) The computer readable medium of claim 54 wherein the message is a resilient packet ring (RPR) fairness message.

57. (Original) The computer readable medium of claim 54 further comprising program instructions operable to implement:  
determining an extent to which a data buffer associated with the client of the first MAC device contains data; and  
preparing the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device based on the extent to which the data buffer associated with the client of the first MAC device contains data.

58. (Original) The computer readable medium of claim 57 further comprising program instructions operable to implement:  
transmitting, to the first MAC device, the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device.

59. (Original) The computer readable medium of claim 54 wherein the message further includes a MAC device address.

60. (Original) The computer readable medium of claim 59 wherein the MAC device address corresponds to one of the first MAC device, the second MAC device, and another MAC device.

61. (Original) The computer readable medium of claim 54 wherein the indication to the second MAC device to change the rate at which the second MAC device transmits

data includes at least one of: a MAC device address, a data transmission rate, a ramp factor, and a flag.

62. (Original) The computer readable medium of claim 54 wherein the indication to the second MAC device to change the rate at which the second MAC device transmits data includes a data transmission rate, the method further comprising:

determining the data transmission rate.

63. (Original) The computer readable medium of claim 54 further comprising program instructions operable to implement at least one of:

calculating the data transmission rate;

selecting a value for the data transmission rate; and

determining a ramp factor.

64. (Original) The computer readable medium of claim 54 further comprising program instructions operable to implement:

transmitting the message from the second MAC device to a third MAC device.

65. (Original) The computer readable medium of claim 54 wherein the information indicating the need to change the amount of data being transmitted through the first MAC device to the client of the first MAC device includes at least one of: a data transmission rate, a counter value, a message indicating that a buffer threshold has been exceeded, and a signal from the client of the first MAC.

66. (Original) The computer readable medium of claim 54 wherein:

the information indicating the need to change the amount of data being

transmitted through the first MAC device to the client of the first MAC device further comprises at least one of: information indicating the need to reduce the amount of data being transmitted, and information indicating the need to increase the amount of data being transmitted; and

the indication to the second MAC device to change the rate at which the second MAC device transmits data further comprises at least one of: an indication

to the second MAC device to reduce the rate at which the second MAC device transmits data, and an indication to the second MAC device to increase the rate at which the second MAC device transmits data.